

SHOT BLASTING MACHINE

**EST 6X15**



**CYM** MATERIALES S.A.  
SOLUCIONES INDUSTRIALES


## RELEVANT FEATURES

- Automatic shot blasting process, does not require skilled labor
- Handle profiles up to 60-inch (1.5 m) X 31-inch (0.8 m), including welded structures, beams, angles, bars and tubes
- Eight blasting turbines positioned inclined from the passage of parts producing up to white metal finish conditions
- For long life, the blast cabinet is made of steel 1010 with internal layer of manganese Steel (11/14%)
- Additionally, reinforcement in hot areas with high chrome cast steel plates ( $\geq 64Rc$  hardness)
- Blowers and external auger for the return of shot accumulated in blasted profiles
- Highly efficient abrasive recovery and separation system to prolong shot life
- Complete state-of-the-art air filter unit guarantee a dust free environment.
- Constructed in compliance with CE or NEMA standard regulations.
- Optional
  - Electric motion detection sensor for elevator belt, screw and roller conveyor
  - Abrasive flow valve control with electrical linear actuators controlled by HMI
  - Transfer for loading and unloading parts

## EST 6X15



Maximum Profile Height	1550 mm - 60"
Maximum Profile Width	800 mm - 31"
Minimum Work Piece Length	3 m - 118"
Maximum Work Piece Length	Conforme requerimiento
Maximum Weight of Work Piece	560 kgs/m - 1230 lb/m
Working speed	0.5 to 2m /min - 20" to 6.5 ft/min
Number of Blast Wheel / Drive	8 x 15 HP - 11.5 Kw
Abrasive Flow Per Turbine	160 Kgs/min - 353 lb/min
Total Abrasive Flow	640 kgs/min - 1412 lb/m
Dust Collector	192 m3/min - 6780 cfm
Total installed power	133.5 HP - 122.62 Kw



## FACTORY AND HEADQUARTERS

Brig. Estanislao Lopez N° 6

[S2108AIB] Soldini - Santa Fé - Argentina

☎ +54 341 490 1100 / 📞 +54 9 341 515-0249

info@cym.com.ar



www.cym.com.ar